



P.O. Box 3019 • 4 Shoham St.  
Caesarea Industrial Park • Israel 38900  
Tel: +972-4-6272-470  
Fax: +972-4-6272-465 • Email: info@elspec-ltd.com



## PPQ 306 Specifications

August 2003 Rev 1.0

Measurement Specifications	See PQA catalog model 311-2N.
LCD Display Size	94x76 mm
LCD Display Resolution	Graphic 160x128 pixels
LCD Display Type	Black/White, FSTN, LED backlight
Ambient Temperature	-20°C - +55°C
Storage Temperature	-25°C - +65°C
Computer Software	PowerIQ Professional included.
Input Channels	10 4×Voltage Channels 3×Current Inputs (./5A) 3×Current Inputs (mA/mV)
Dimensions (closed)	270 × 246 × 123 mm [W×D×H]
Weight	1.9 kg
Power Supply	100-240V ~ 0.2A 50-60Hz
Direct Voltage Measurement	347/600 VAC Max.
EMC Compatibility*	EN61000-4-2/3/4/5, ENV50204, ENV50141
Safety Standards*	EN61010-1, EN50439-1
Communication	Elcom (Elspec's Protocol)
Power Consumption	< 3 VA
Harmonic Analysis	1 through 63 <sup>rd</sup>

\* Based on design guidelines. Standards tests were not performed yet.